



Av. Europa, nº 12
17800 OLOT
(Girona) SPAIN

Tel. (+ 34) 972 265 100
Fax (+ 34) 972 266 366

xucla@xucla.es
www.xucla.es



Code	Description
013272G	GAS OIL CARTS WASHING MACHINE 50/60 UN.

Tecnic description

PROCESS:

Load zone.

Waiting zone.

Washing with hot and soapy water.

Rising with water non-reusable direct mains water.

Unload zone.

GENERAL FEATURES

Construction in stainless steel AISI 304

Ceramic ball blasted finish.

Total sizes:

Length 9.500 mm.

Width 2.120 mm.

Height 2.250 mm + 900mm build under.

Machine delivery in two parts, upper and lower, which are screwed on 5 double doors made of PVC and stainless steel brackets with soft closing

Standing on 12 adjustable feet type M20.

Level of acoustic pressure according to the CE.

Production from 50 to 60 units/hour depending on their dirtiness.

Carts sizes: 1.260 x 800 x 1.900mm.

WASHING

780 liters water-tank.

Water feeding by ball-valve and 3/4 " stainless steel floating buoy 3/4 "

Emergency stoppage for pump protection.

1 1/4" stainless steel purge tap type ball and emptying peep-hole of 210x170 mm.

Overflow with exit to outside.

Removable box-type filter with 1 mm triangular profile grille, with extraction of solids to the overflow

Inspection and tank's cleaning cover .

112 sprinklers, distributed in 14 easily detachable bars manually

Flat jet sprinklers, 3mm diameter

Stainless steel motor pump 22 Kw, volume 105 m3/h and pressure 5 Kg/s.q.cm.

Water-tank heating by exchange of warm air-water by gas oil combustion camera.

Burner of gas oil 10 l/hour. Smoke exit excluded.

Temperature controlled by an electronic- digital regulator

Glycerine manometer.

RINSING

Rinsing with non-reusable direct mains water

Water feeding controlled by ball-valve of 3/4 ".

28 flat jet stainless steel sprinklers distributed in two rings



Av. Europa, nº 12
17800 OLOT
(Girona) SPAIN

Tel. (+ 34) 972 265 100
Fax (+ 34) 972 266 366

xucla@xucla.es
www.xucla.es



INTERIOR TRANSPORT

Double dragging chain type charnela inox 152mm width, 38mm pass
Traction by nylon pinions.
The chain slides on friction guide.
Bearings in thermoplastic box
Variable speed from 1 to 3m/min.
Driving by moto reducer of aluminium of 0.37 kW.

ANOTHER

Two steam exits placed on the waiting area and on the rinsing area, ready to install steam extractors
Double lateral guide in polyethylene of friction

ELECTRICAL SWITCHBOARD

Electrical switchboard in fibre, IP-65, built-in inside stainless box with methacrylate window.
Speedy chain electronic variator
Emergency stoppage switch outside the cupboard
Protected motor pump. Running luminous indicators. General switch, push-buttons.
Electronical-digital temperature control with bore PT-100.
MOELLER material: motor-protections, contractors, terminals and switches (Sprecher).
Handling to 24 VAC.

CONSUMES

Water:
Filling the tank 780 l.
Rinsing (adjustable) 10-20 l / min.
Electricity:
Motor pump 22 Kw.
Chain moto reducer 0.73 Kw.
Moto reducer filter 0.18 Kw.
Gas oil: 9 l/h.

CONNECTIONS

Water: $\frac{3}{4}$ ", $\frac{1}{2}$ "
Electricity: 400 III + N + T (50 Hz)
Burner: $\frac{3}{8}$ ".